



- NOTE:
- Electrical Characteristics:
    - 1-1: Current Rating: 5A For Pin(A4,A9,B4,B9)  
1.25A For Pin(B5)  
0.25A For Others Pin
    - 1-2: VOLTAGE RATING: 20V AC/DC.
    - 1-3: Insulation Resistance: 100MΩ Min.
    - 1-4: Contact Resistance:  
VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX.  
SHIELD: 50mΩ/MAX.  
SHIELD: ILCR MAX. CHANGE OF ALL PINS: 10mΩ.
    - 1-5: Dielectric Withstanding Voltage: 100V/AC 1Minute
  - Mechanical Characteristics:
    - Insertion Force: 5~20N
    - Extraction Force: Initial: 8~20N  
After durability: 6~20N
    - Durability :10000 Cycles
  - Operating Temperature: -30°C TO +85°C

设计:	Arvin: 2016.03.08	范围 Range	公差 Tolerance
审核:	Arvin:	X.X ±	X.X ±0.30
校对:	Ru yi:	X.XX ±	X.XX ±0.20
比例:	视角关系:	X.XXX ±	X.XXX ±0.10
版次:	图框大小: A4	Angle ±	Angle ±5°

东莞市恒祺电子科技有限公司

名称: TYPE-C      料号:

形号: 16PIN45W立式侧插

共 张 , 第 张      备注: