



PCB LAYOUT 图仅供参考

- Note:
1. Material:
 - 1.1 Housing: PA9T
 - 1.2 Contact: C7025, t=0.20mm
 - 1.3 Shell: Kirsite
 2. ELECTRICAL:
 - 2-1: CURRENT RATING: 3A
 - 2-2: INITIAL CONTACT RESISTANCE : 40 MEGOHMS
 - 2-3: DIELECTRIC WITHSTANDING VOLTAGE: 100V AC MIN;
 3. MECHANICAL CHARACTERISTICS:
 - 3-1: MATING FORCE: 5~20N
 - 3-2: UNMATING FORCE: 8~20N(INITIAL), 6~20N(AFTER 10000 CYCLES)
 - 3-3: FREQUENCY: 200±50 CYCLES / HOUR, 10000 CYCLES
 - 3-4: OPERATING TEMPERATURE ; -40°~80°.
 - 4: WATERPROOF: IP-X7.

设计:	Arvin: 2016.03.08	范围 Range	公差 Tolerance	东莞市恒祺电子科技有限公司	
审核:	Arvin:	X.X ±	X.X ±0.30		
校对:	Ru yi:	X.XX ±	X.XX ±0.20	名称: TYPE-C	料号:
比例:	视角关系:	X.XXX ±	X.XXX ±0.10	形号: 6PIN沉板0.8防水	
版次:	图框大小: A4	Angle ±	Angle ±5°	共 张 , 第 张	备注: